


MY25 MAVERICK R MAX X RS 999T DCT SAS



 Dusty Navy & Legion Red

ENGINES	999T DCT
Type	240 hp, Rotax 999T DCT engine, 999cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Rotax DCT, 7 Speed with High & Extra Low range
Drive Train	Lockable front differential with exclusive Smart-Lok* True 2WD / 4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL
Power Steering	Gen 2 Tri-mode DPS High torque
Front Suspension	Forged Aluminum heavy duty Tall Knuckle Double A-arm with sway bar / 24 in. (61 cm) suspension travel
Front Shocks	FOX† 2.5 PODIUM† RC2† Piggyback with bypass and Smart-Shox** Technology featuring Live Valve Gen 3 (Dual Valve compression & rebound)
Rear Suspension	4 Link Trailing arm with Forged Aluminum heavy duty Tall Knuckle / 24 in. (61 cm) suspension travel
Rear Shocks	FOX† 3.0 PODIUM† Piggyback with bypass and Smart-Shox** Technology featuring Live Valve Gen 3 (Dual Valve compression & rebound)
TIRES / WHEELS	
Front / Rear Tires	XPS Trac Force 32 x 10 x 16 in.
Wheels	16 in. Aluminum Flow Formed Beadlock
BRAKES	
Front	32 mm hydraulic triple piston caliper with a 265 mm disc
Rear	32 mm hydraulic twin piston caliper with a 255 mm disc

PACKAGE HIGHLIGHTS

- 77 in. 4 Link Trailing arm with aluminum HD tall knuckle
- Smart-Lok™** front differential
- FOX† 3.0 PODIUM† Piggyback with bypass and Smart-Shox** Technology featuring Live Valve gen 3 (Dual Valve compression & rebound)
- 10.25 in. touchscreen display
- 32 in. ITP Tenacity XNR tires
- 16 in. Flow Formed Beadlock wheels
- Front and rear camera
- Telescopic steering wheel with infotainment controls
- Full hard roof
- Full HD HMW plastic skid plate
- Rock guard
- 4-point harness with shoulder pads
- Premium high-performance LED headlights
- Can-Am LED signature
- Center dashboard storage with cell phone holder
- X-package graphics/seats
- 1700-W Magneto
- RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button

DIMENSIONS / CAPACITIES

Cage	High strength steel (Dual phase) steel tubing and stampings
Estimated Dry Weight*	2,660 lb (1210 kg)
L x W x H	175 x 78.1 x 69.2 in. (444.7 x 198.4 x 175.7 cm.)
Wheelbase	142.5 in. (365 cm)
Ground Clearance	17 in. (43.2 cm)
Cargo Box Capacity	200 lb (90 kg)
Storage Capacity	Total: 2.1 gal (8.1 L)
Fuel Capacity	13.2 Gal (50 L)
Gauge	4.5 in. wide digital display with keypad & 10.25 in. touchscreen display
Magneto	1700-W
Instrumentation	USB A (Charging port & Communication port) DC outlet (10-A)
Lighting	Premium high-performance LED headlights Can-Am LED signature
Winch	4,500 lb (2,041 kg) winch ready bumper (not installed)
Protection	Full hard roof Premium half doors Front lower deflector Front / Rear anchor Full HD HMW plastic skid plate Rock guard

WARRANTY & EXTENDED SERVICE

Factory warranty	2-year BRP limited warranty
------------------	-----------------------------



REQUEST A QUOTE



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †Visco-Lok is a trademark of GKN ViscoDrive GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.